



SPRAYS & NOZZLES BUBBLERS & BED SPRAYS

Pressure Compensating Bubbler

FLOW
1.0 GPM (3.8 lpm)

SPACING
1 - 3' (0.3 - 0.9 m)

PRESSURE
15 - 45 PSI (1.1 - 3.2 Kg/cm2)

CONSTRUCTION
Durable ABS plastic housing. Pressure compensating device is made of long life Buna-N rubber

(1/2" IPS connection)



NO. 106 PRESSURE COMPENSATING BUBBLER

No. 106 provides a soft, bubbling action for deep soaking. Ideal for planter boxes, tree wells or similar areas when proper drainage is available.

FEATURES

- Pressure compensating bubbler with trickle Pattern
- Inlet filter screen to prevent clogging
- Durable engineering-grade plastic construction
- Application for tree wells and bed areas

PRESSURE COMPENSATING BUBBLER SPECIFICATIONS

MODEL	DESCRIPTION
106-100	1.0 GPM

Adjustable Bubbler

FLOW
1.1 - 2.3 GPM (0.25 - 0.52 m3/hr)

SPACING
1 - 3' (0.3 - 0.9 m)

PRESSURE
110 - 60 PSI (1.1 - 4.2 BAR)

CONSTRUCTION
Durable ABS plastic housing. Pressure compensating device is made of long life Buna-N rubber

(1/2" IPS connection)



NO. 102 & 133 ADJUSTABLE BUBBLERS

No. 102 and 133 are the perfect choice for all applications where economy and/or higher flows are required. Ideal for planter boxes, tree wells or similar areas when proper drainage is available.

FEATURES

- Umbrella Pattern, full circle bubbler
- Durable engineering-grade plastic construction
- Inlet filter screen to prevent clogging
- Application for free wells and bed areas

NO. 102 & 133 PERFORMANCE DATA

Pressure		Flow			
		Min		Max	
PSI	Kg/cm2	GPM	lpm	GPM	lpm
20	1.4	1.3	4.9	3.0	11.4
30	2.2	1.6	6.1	4.0	15.1
45	3.2	2.0	7.6	4.5	17.0

* Flow rate for factory adjusted setting.

ADJUSTABLE BUBBLER SPECIFICATIONS

MODEL	DESCRIPTION
102	Screw adjustment
133	Knob adjustment



Save Water. Give Life.

10 gallons
given per nozzle