



CONTROLLER OVERVIEW

ProLine®



Affordable controller with professional features
Advanced programming features

PL800 PL1600 PL4800

SmartLine®



Two controllers in one with two modes:
Basic and Smart
ET Based scheduling
SmartLink compatible

SL1600 SL4800 SL1620 SL9600

SoloRain®



Battery powered
Valve mounted
Single zone

8014ESR-SOLORAIN

Base # of Zones	4	4	12	4	12	20	48 Fixed 96 Fixed	1
Maximum # of Zones	8	16	48	16	48	20	48/96	1
Compatible Expansion Modules	SLM2	SLM4 SLM12-1600	SLM12-4800	SLM4 SLM12-1600	SLM12-4800	–	–	
Outdoor Rated	Indoor only	✓	✓	✓	✓	✓	✓	✓
Electrical	120VAC	120VAC	120VAC	120VAC	120VAC	120VAC	120VAC	3.6V Lithium Battery
Lock		✓	✓	✓	✓	✓	✓	
Programs	4	4	4	4	4	4	4	6
Start Times	8	8	8	8	8	8	8	1
Simultaneous Solenoid Operation	3	3	5	3	5	3	5	1
SmartLink Compatible				✓	✓	✓	✓	
Backlit LCD		✓	✓	✓	✓	✓	✓	
SmartWire Compatible							✓	
ET Based Scheduling				✓	✓	✓	✓	



Save Water. Give Life.

Learn More

weathermatic.com/our-cause