



# QUICK COUPLING VALVES

- ACME® threads standard for slow and steady flow control instead of immediate on/off.
- Rubber cover
- Optional locking cover available
- Optional lavender rubber cover identifies reclaimed water site - molded in "RECLAIMED WATER - DO NOT DRINK": in English and Spanish.



### 7642-QCVKEY

Quick Coupling Valve with Yellow Non-Locking Cover, 1" NPT (25.4 mm)



### 7643-QCVLYEL

Quick Coupling Valve with Yellow Locking Cover, 1" NPT (25.4 mm)



### 7644-QCVNP

Quick Coupling Valve with Lavender Non-Locking Cover, 1" NPT (25.4 mm)



### 7645-QCVLNP

Quick Coupling Valve with Lavender Locking Cover, 1" NPT (25.4 mm)

|                      |   |                                 |                                 |                                 |
|----------------------|---|---------------------------------|---------------------------------|---------------------------------|
| <b>Flow Range</b>    | Max Capacity: 20 GPM (75.7 L/M)                                     | Max Capacity: 20 GPM (75.7 L/M) | Max Capacity: 20 GPM (75.7 L/M) | Max Capacity: 20 GPM (75.7 L/M) |
| <b>Pressure</b>      | Max: 125 PSI (8.6 BAR)  | Max: 125 PSI (8.6 BAR)          | Max: 125 PSI (8.6 BAR)          | Max: 125 PSI (8.6 BAR)          |
| <b>Rubber Cover</b>  | ✓   | ✓                               | ✓                               | ✓                               |
| <b>Locking Cover</b> |   | ✓                               |                                 | ✓                               |
| <b>Warning Cover</b> |   |                                 | ✓                               | ✓                               |
| <b>Dimensions</b>    | Bottom Pipe Thread: 1" (25.4 mm)<br>Overall Height: 3 3/4" (9.5 cm) |                                 |                                 |                                 |

## QUICK COUPLING KEY SPECIFICATIONS

| MODEL       | DESCRIPTION                                 | FOR VALVE MODELS | MALE             | FEMALE           | HEIGHT            |
|-------------|---|------------------|------------------|------------------|-------------------|
| 7640-QCVKEY | Quick Coupling Key, 3/4" male x 1/2" female | All models       | 3/4"<br>19.05 mm | 1/2"<br>12.7 mm  | 5 1/4"<br>13.3 cm |
| 7641-QCVKEY | Quick Coupling Key, 1" male x 3/4" female   | All models       | 1"<br>25.4 mm    | 3/4"<br>19.05 mm | 5 1/4"<br>13.3 cm |
| 8649-QCVKEY | QCV Locking Cover Key                       |                  |                  |                  |                   |



7641-QCVKEY



8649-QCVKEY



7640-QCVKEY

## QUICK COUPLER KEYS SWIVEL ELBOWS (NPT) SPECIFICATIONS

| MODEL    | DESCRIPTION                      |
|----------|----------------------------------|
| 8810-ELL | 3/4" Female NPT x 3/4" Male Hose |
| 8811-ELL | 1" Female NPT x 3/4" Male Hose   |
| 8812-ELL | 1" Female NPT x 1" Male Hose     |



8810-ELL



8811-ELL



8812-ELL

