

Technical Specifications

SLPED-ENC POWDER-COATED METAL PEDESTAL ENCLOSURE

FEATURES

- SLPED-ENC-M-1600 fits all SL1600 Series controllers
- SLPED-ENC-M-4800 fits all SL4800 and SL9600TW Series controllers
- 16 gauge metal construction with powder-coated finish
- 2-part cabinet and pedestal mount model
- Filtered louvers for ventilation
- Cam style keylock
- Weather-resistant
- NEMA TYPE 3R rated with SmartLine controller installed
- SLPED-ENC-M-1600 Dimensions – 13 ¼" W x 44¼" H x 6 ¼" D (33,66 cm x 112,40 cm x 15,88 cm)
- SLPED-ENC-M-4800 Dimensions – 19 ½" W x 44¼" H x 7 ¾" D (49,53 cm x 112,40 cm x 19,69 cm)

SPECIFICATION

- SLPED-ENC POWDER-COATED METAL ENCLOSURES shall be model SLPED-ENC-M-1600 or SLPED-ENC-M-4800 as manufactured by Weathermatic Sprinkler Division of Telsco Industries.
- **CONSTRUCTION:** Enclosures shall be fabricated from 16 gauge metal with a powder-coated finish. Enclosures shall be NEMA type 3R rated weather-resistant with filtered louvers for cross-ventilation.

A removable powder-coated metal door shall be mounted to the front of the cabinet and include a cam style keylock to restrict access to the cabinet.

SLPED-ENC-M-1600 Enclosure shall measure 13 ¼" wide x 44 ¼" high x 6 ¼" deep.

SLPED-ENC-M-4800 Enclosure shall measure 19 ½" wide x 44 ¼" high x 7 ¾" deep.

WARRANTY: Enclosures shall have a manufacturer's limited warranty of two (2) years.

